

UHD Signage UH5J-H

New High Haze UHD Standard Signage





Mobile Content

Management



webOS Smart Platform

Meeting Room Solution

UH5J-H	
Screen Size	98" / 86" / 75" / 65" / 55" / 49" / 43"
Native Resolution	3,840 × 2,160 (UHD)
Bezel Color	Black
Brightness	500 nit (Typ.)
Bezel	98" / 75" : 14.9 mm (Even bezel) 86" : 14.3 mm (Even bezel) 65" / 55" / 49" : 9.9 mm (T/R/L), 14.4 mm (B) 43" : 8.4 mm (T/R/L), 14.4 mm (B)
Depth	98" : 86.1 mm 86" : 60.6 mm 75" : 57.9 mm 65" / 55" / 49" / 43" : 39.9 mm

hello@infopolis.hu

https://infopolis.hu





Appropriate Display Brightness

With a recommend brightness of 500 cd/m^2 for indoor display, the UH5J-H series clearly delivers content and attracts public attention, making it the most suitable display for marketing in meeting rooms, airports, retail, shopping malls, etc.

* Actual images available may differ from the example images shown.



High-Performance with webOS

LG webOS platform enhances user convenience with intuitive GUI and simple app development tools.



Conformal Coating

In various places the UH5J-H series is unable to avoid exposure to environments containing dust, humidity, etc. which may hamper performance over time. The conformal coating on power board reduces these risks by protecting UH5J-H series from salt, dust, iron powder, humidity, etc.

* Actual images (signage display) available may differ from the example images shown.



Mobile Content Management

You can create a store profile and get template recommendations using the Promota* app. Users can customize templates as needed and easily create and manage content not only on PCs but also on mobile devices.

* LG Promota is can be downloaded from the App Store and Google Play store. (Not available for Europe/CIS Region)

* In Korea, the name is not Promota, but Mustard.

hello@infopolis.hu

https://infopolis.hu





IP5x Certified Design

The IP5x Dust-Proof Certification ensures that the product is protected from dust, reducing the risk of performance degradation.



Compatible with AV Control System

The UH5J-H series has supported Crestron Connected® for high compatibility with professional AV controls to achieve seamless integration and automated control*, boosting business management efficiency.

* Network based control

CONNECTIVITY

3" le					Bottom				
DP IN (4K@6	HDMI OUT	DVI-D IN	USB 2.0 IN 5V == 0.5A	S-232C RS-232C IN OUT	AUDIO IN OUT	LAN 북북	HDMI IN 1 (4K@60Hz)	HDMI IN 2 (4K@60Hz, ARC)	IR&LIGHT SENSOR
0 0	8	4	5	6 7	89	0	0	D	B
5" / 75" le					Detterr				
DP IN HDMI		DVI-D IN	USB 2.0 IN 5V == 0.5A	S-232C RS-232C IN OUT	Bottom	LAN 무무	HDMI IN 1 (4K@60Hz)	HDMI IN 2 (4K@60Hz, ARC)	
0 2	8	4	5	6 7	89	0	0	Ð	B
• •		Ø	9	6 0	89	Ū	0	Ø	₿
" / 55" / 4	9" / 43"	HDMI IN 2 HDM	II IN 3 DP IN	HDMI OUT	DVI-D	D IN IR&LL SEN:	C		-
" / 55" / 4	9" / 43"	HDMI IN 2 (44@ C	DP IN		DVI-D		GHT SOR SU≡ 0.5A	AUDIO IN O	-232C RS-232C IN OUT OUT
" / 55" / 4	9" / 43"	HDMI IN 2 (@ootr, ARC)	II IN 3 DP IN	HDMI OUT	DVI-D		GHT USB 2.0 IN SOR SV = 0.5A	AUDIO IN O	-
" / 55" / 4	9" / 43"	HDMI IN 2 (44@ C	DP IN		DVI-D		GHT SOR SU≡ 0.5A	AUDIO IN 3 9	-232C RS-232C IN OUT OUT
" / 55" / 4	9" / 43"	HDMI IN 2 (44@ C	DP IN				GHT SOR SUSB 2.0 IN SV = 0.5A ₩ 5	AUDIO IN 89	-232C RS-232C IN OUT OUT
" / 55" / 4	9" / 43" HDMIIN1 (4K@OOH) 10	HDMI IN 2 (execont, Arc)	DVI-D IN	HDMI OUT	DVI- DVI- C 4 7 RS-232C OU		GHT SOR SUSB 2:0 IN SUSB 2:0	AUDIO IN 8 9 AUDIO 8 9	-232C N OUT OUT OUT OUT OUT

Download LG C-Display+ Mobile App Google Play Store

hello@infopolis.hu

www.lg.com/global/business/information-display
www.youtube.com/c/LGECommercialDisplay
www.fiacebook.com/LGInformationDisplay
www.linkedin.com/company/lginformationdisplay
twitter.com/LG_ID_HQ

LG may make changes to specifications and product descriptions without notice. Copyright © 2022 LG Electronics Inc. All rights reserved. "LG Life's Good" is a registered trademark of LG Corp. The names of products and brands mentioned here may be the trademarks of their respective owners.



https://infopolis.hu